


| Poziție | Cant. | Descriere |
|---------|-------|--|
| | 1 | <p>SOLOLIFT2 WC-3</p>  <p>Notă! Poza de produs poate diferi de produsul actual</p> <p>Nr. Produs: 97775315</p> <p>Sololift2 WC-3 is a small, compact automatic lifting station suitable for pumping of wastewater off places in private dwellings where wastewater cannot be led directly to the sewer by means of a natural downward slope.</p> <p>Sololift2 WC-3 is suitable for pumping wastewater from a toilet containing toilet paper and faeces with additional connections on the lid and to the sides of the tank for e.g. washbasin, shower or bidet.</p> <p>The pumping of liquids containing other material may cause faults and limit the scope of guarantee.</p> <p>Sololift2 WC-3 is typically used to dewater:</p> <ul style="list-style-type: none"> • toilet, washbasin, shower and bidet in basements below sewer level, <p>in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established.</p> <p>Extremely low switching levels for lowest construction heights, advantageously in case of connection of a shower receptor.</p> <p>The compact lifting station is equipped with</p> <ul style="list-style-type: none"> - Cable with or without plug (see technical data) - Horizontal or vertical fastening possibility of discharge hose connector with several adaptors for pipes with Ø22-40mm <p>-Integrated non return valve</p> <ul style="list-style-type: none"> - Dry and high performance motor unit incl. thermal protection, pressure switch and controller - DN100 toilet connection hose - Two flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40 - Slot for an alarm board with buzzer (accessory) - Manual anti clogging function and separate drain connection for service - Venting valve with overflow protection - Uplift fixation clips <p>Design according to EN12050-3 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.</p> <p>Note: The discharge adaptor can be mounted vertical or horizontal. Vertical installation increase the flow (s. databooklet and curves)</p> <p>Liquid:</p> <p>Lichide pompate: orice vâscozități fluid</p> <p>Temperatura maximă a lichidului: 50 °C</p> <p>Densitate: 998.2 kg/m³</p> <p>Technical:</p> <p>Debitul curent calculat: 1.03 l/s</p> <p>Înălțimea de pompare rezultată pentru pompă: 6.862 m</p> |

| Poziție | Cant. | Descriere |
|---------|-------|--|
| | | <p>Aprobări pe etichetă: CE,TR,LGA,VDEEMV,VDE Toleranța curbelor: ISO9906:2012 3B</p> <p>Materials: Rezervor: PLASTIC</p> <p>Instalație: Aspirație pompă: 32/36/40, 36/40/50, DN 100 Refulare pompă: 22/25/28/32/36/40 Număr de conductori: 3X0,75MM2</p> <p>Electrical data: Puterea de întarare - P1: 620 W Frecvența rețelei electrice: 50 Hz Tensiune nominală: 1 x 220-240 V Curent nominal: 3 A Cos fi - factor de putere: 0,92 Turație nominală: 2800 rpm Grad de protecție (IEC 34-5): IP44 Clasă de izolare (IEC 85): F Lungimea cablului: 1.2 m Tip cablu: H05VV-F Tip de conectare cablu: SCHUKO</p> <p>Others: Greutate netă: 7.3 kg Greutate brută: 10 kg</p> |

| Descriere | Valori și tipuri |
|--|----------------------------|
| Informații generale: | |
| Nume produs:: | SOLOLIFT2 WC-3 |
| Nr. produs:: | 97775315 |
| Numărul EAN:: | 5710624187241 |
| Technical: | |
| Debitul curent calculat: | 1.03 l/s |
| Înălțimea de pompare rezultată pentru pompă: | 6.862 m |
| Înălțime de pompare max.: | 8.5 m |
| Aprobări pe etichetă: | CE, TR, LGA, VDEEMV, VDE |
| Toleranța curbelor: | ISO9906:2012 3B |
| Materials: | |
| Rezervor: | PLASTIC |
| Instalație: | |
| Aspirație pompă: | 32/36/40, 36/40/50, DN 100 |
| Refulare pompă: | 22/25/28/32/36/40 |
| Număr de conductori: | 3X0,75MM2 |
| Liquid: | |
| Lichide pompate: | orice vâscozități fluid |
| Temperatura maximă a lichidului: | 50 °C |
| Densitate: | 998.2 kg/m³ |
| Electrical data: | |
| Puterea de intrare - P1: | 620 W |
| Frecvența rețelei electrice: | 50 Hz |
| Tensiune nominală: | 1 x 220-240 V |
| Curent nominal: | 3 A |
| Cos fi - factor de putere: | 0,92 |
| Turație nominală: | 2800 rpm |
| Grad de protecție (IEC 34-5): | IP44 |
| Clasă de izolare (IEC 85): | F |
| Protecție termică: | THERMIK S06-150-05 |
| Lungimea cablului: | 1.2 m |
| Tip cablu: | H05VV-F |
| Tip de conectare cablu: | SCHUKO |
| Others: | |
| Greutate netă: | 7.3 kg |
| Greutate brută: | 10 kg |
| Gamă produs: | Internațional |

